

SPECIFICATIONS

Gendai - charred and brushed once

"Modern" dark, with a smooth, silky look

MATERIAL PROPERTIES:

Species: Japanese cypress (Cryptomeria japonica)

Origin: Origin: Japan, PEFC-/SGEC-certified

Hardness: Very soft - 320 - 510 (Janka)

Weight: Light - 360 - 380 kg/m³

Specific gravity: 0,33 - 0,36 R₁₂

Moisture content: 11-14%

Durability: Durable - decay resistance class 2

Use class rating Exterior, above ground, exposed to

(EN-335): weather - Use Class 3

Fire resistance D-s2, d0 (general rating, BS class 3)

(EN-13501):

Squared timber: Charred and brushed four sides on

request (90/60/45x30)

GENERAL INFORMATION:

Please add a healthy overage ranging 10-20% to Overage:

your order as shipping additional material can be

EUROPE

very expensive.

When calculating the area of cladding required please pay attention to the covering width of the lining.

Furring: Generally applied to ventilated curtain walls or rain-

screens. It should be ensured that the cladding can

dry and waterlogging is avoided.

Fasteners: Stainless steel ring/screw-shank headed nails

or wood screws (exterior), pin nails (interior).

Installation Vertical, horizontal, or diagonal layout possible,

layout: open or closed screen.

Pre-Our pre-finishes are coated on the cladding surface.

finishes: Coating of the edges or backs on demand.

Touch-up oil is supplied free of charge.

AVAILABLE PROFILES AND DIMENSIONS:

STANDARD SHIPLAP DIMENSIONS 145 mm width (Reveal 135 mm), 3970 mm length 195 mm width (Reveal 185 mm), 3970 mm length Reveal 135 mm 10 mm 145 mm 195 mm

STANDARD SQUARE EDGE DIMENSIONS 145 mm width, 3970 mm length 195 mm width, 3970 mm length 89 mm width, 3970 mm length 15 mm 145 mm 195 mm 89 mm

AVAILABLE STANDARD COLOURS:



#101 transparent (Int/Ext)



#121 light oak (Int/Ext)

Transparent/light pigmentations without UV blocker (like #101 and 21) let Gendai lighten in first months





#331 ebony (Int/Ext)



#132 ebony (Int/Ext)



PRODUCT DOES NOT SHED SOOT AFTER INSTALLATION